



Teniendo NO.	Dimensiones del límite [mm]			Velocidad límite (rpm)		Capacidades de carga básica (kN)		Masa (kilogramo)
	re:	RE:	SEGUNDO:	Grasa	Petróleo	Cr	Cor	Referir
NJ1004ECP	20	42	12	10.5	9.2	13000	17000	0.09
NJ1004ECJ	20	42	12	10.5	9.2	13000	17000	0.09
NJ1004ECM	20	42	12	10.5	9.2	13000	17000	0.09
NJ1005ECP	25	47	12	11	10.2	11000	15000	0.1
NJ1005ECJ	25	47	12	11	10.2	11000	15000	0.1
NJ1005ECM	25	47	12	11	10.2	11000	15000	0.1
NJ1006ECP	30	55	13	13	12.8	9500	12000	0.12
NJ1006ECJ	30	55	13	13	12.8	9500	12000	0.12
NJ1006ECM	30	55	13	13	12.8	9500	12000	0.12
NJ1007ECP	35	62	14	19.5	18.8	8500	11000	0.16
NJ1007ECJ	35	62	14	19.5	18.8	8500	11000	0.16
NJ1007ECM	35	62	14	19.5	18.8	8500	11000	0.16
NJ1008ECP	40	68	15	21.2	22	7500	9500	0.22
NJ1008ECJ	40	68	15	21.2	22	7500	9500	0.22
NJ1008ECM	40	68	15	21.2	22	7500	9500	0.22
NJ1009ECP	45	75	16	23.2	23.8	6500	8500	0.26
NJ1009ECJ	45	75	16	23.2	23.8	6500	8500	0.26
NJ1009ECM	45	75	16	23.2	23.8	6500	8500	0.26
NJ1010ECP	50	80	16	25	27.5	6300	8000	0.31
NJ1010ECJ	50	80	16	25	27.5	6300	8000	0.31
NJ1010ECM	50	80	16	25	27.5	6300	8000	0.31
NJ1011ECP	55	90	18	35.8	40	5600	7000	0.45
NJ1011ECJ	55	90	18	35.8	40	5600	7000	0.45

Cylindrical roller bearing NJ NF series Bearing manufacturer

NJ1011ECM	55	90	18	35.8	40	5600	7000	0.45
NJ1012ECP	60	95	18	38.5	45	5300	6700	0.48
NJ1012ECJ	60	95	18	38.5	45	5300	6700	0.48
NJ1012ECM	60	95	18	38.5	45	5300	6700	0.48
NJ1013ECP	65	100	18	39	46.5	4800	6000	0.51
NJ1013ECJ	65	100	18	39	46.5	4800	6000	0.51
NJ1013ECM	65	100	18	39	46.5	4800	6000	0.51