

## 4300 Series



Teniendo No.	Dimensiones del límite [mm]				Capacidades de carga básica (kN)		Velocidad límite (rpm)		Masa
	re:	RE:	SEGUNDO:	rs min	Dinámico (Cr)	Estático (Cor)	Grasa	Petróleo	Kg
4300	10	35	17	0.6	14.3	8.9	18600	17500	0.091
4301	12	37	17	1	13	7.8	15000	16500	0.092
4302	15	42	17	1	13.1	11.7	12000	15000	0.123
4303	17	47	19	1	16.5	15	10000	13000	0.171
4304	20	52	21	1.1	19.5	17	9500	12000	0.227
4305	25	62	24	1.1	26.3	25.7	8500	10000	0.365
4306	30	72	27	1.1	35.5	35.9	7000	8500	0.542
4307	35	80	31	1.5	40.6	41.8	6300	7500	0.752
4308	40	90	33	1.5	46	48.8	5600	6700	0.958
4309	45	100	36	1.5	57.6	62.4	5000	6000	1.35
4310	50	110	40	2	81.9	69.5	4500	5300	1.7
4311	55	120	43	2	97.5	83	4300	5000	2.15
4312	60	130	46	2.1	112	98	3800	4500	2.65
4313	65	140	48	2.1	121	106	3600	4300	3.25
4314	70	150	51	2.1	138	125	3200	3800	3.95
4315	75	160	55	2.1	156	143	3000	3600	4.8