

Flanged Bearing



Teniendo No.	Dimensiones del límite [mm]					Capacidades de carga básica (kN)	
	re:	RE:	SEGUNDO:	Df	Bf	Dinámico (Cr)	Estático (Cor)
F627zz	7	22	7	25	1.5	2794	1103
F627	7	22	7	25	1.5	2794	1103
F627 2RS	7	22	7	25	1.5	2794	1103
F607zz	7	19	6	22	1.5	1986	717
F607 2RS	7	19	6	22	1.5	1986	717
F607	7	19	6	22	1.5	1986	717
F697zz	7	17	5	19	1.2	1364	575
F697 2RS	7	17	5	19	1.2	1364	575
F697	7	17	5	19	1.2	1364	575
F687zz	7	14	5	16	1.1	997	410
F687 2RS	7	14	5	16	1.1	997	410
F687	7	14	3.5	16	1	997	410
MF137zz	7	13	4	14.6	0.8	460	221
MF137 2RS	7	13	4	14.6	0.8	460	221
MF137	7	13	3	14.2	0.6	460	221
MF117zz	7	11	3	12.2	0.6	387	162
MF117 2RS	7	11	3	12.2	0.6	387	162
MF117	7	11	2.5	12.2	0.6	387	162
F626zz	6	19	6	22	1.5	1986	717
F626 2RS	6	19	6	22	1.5	1986	717
F626	6	19	6	22	1.5	1986	717
F606zz	6	17	6	19	1.2	1924	677
F606 2RS	6	17	6	19	1.2	1924	677
F606	6	17	6	19	1.2	1924	677

Flanged Bearing

F696zz	6	15	5	17	1.2	1139	418
F696 2RS	6	15	5	17	1.2	1139	418
F696	6	15	5	17	1.2	1139	418
F686zz	6	13	5	15	1.1	920	354
F686 2RS	6	13	5	15	1.1	920	354
F686	6	13	3.5	15	1	920	354