

## Double Row Tapered Roller Bearings



Número de rodamiento		Dimensiones básicas		
Tipo 1	Tipo 2	re:	RE:	SEGUNDO:
97514E	352214	70	125	74
97515E	352215	75	130	74.5
187216	187216	80	140	56.75
97516	352216X2	80	140	80
97517EK	352217X2	85	150	84
97518EK	352218X2	90	160	94
97820	97820	100	180	83
97520EK	97520EK	100	180	111
37720	350620D1	100	190	125
97521EK	97521EK	105	190	117
2097722	352122	110	180	95
97522EK	97522EK	120	200	124
2097724	352124	120	200	110
187224E	187224E	120	215	87
97524E	352224	120	215	132
2097926	352926X2	130	180	70
2097126	352026X2	130	200	95
1-7006	1-7006	130	210	64
2097726	352126	130	210	110
97826U	97826U	130	214	115.6
97526	352226X2	130	230	149
37726	350626D1	130	235	145
2097128	352028X2	140	210	95
2097728	352128	140	225	115

## Double Row Tapered Roller Bearings

---

97528E	352228	140	250	153
187328	187328	140	300	154
32930/DF	32930/DF	150	210	76
2097930	352930X2	150	210	80
97830	97830	150	225	112
2097730	352130	150	250	138