

Double Row Tapered Roller Bearing With Two-piece Outer Ring(Inch Series)



Teniendo NO.	Dimensiones del límite [mm]				Diseño	Dimensiones del pilar y del filete (mm)				Valor				Peso (kilogramo)
	re:	RE:	T	C		da (min)	Da max	rb (máx.)	ra (máximo)	mi	Y1	Y2	Y0	Referir
868D/854	101.6	190.5	127	117.475	1	113	168	1.6	3.2	0.33	2	3	2	14.5
868D/854X	101.6	200.025	127	127	1	113	172	1.6	3.2	0.33	2	3	2	18.2
71426D/71750	107.95	190.5	101.6	98.425	1	121	171	1.6	3.2	0.42	1.6	2.4	1.6	11.8
946D/932	107.95	212.725	152.4	142.885	1	123	187	3.2	3.2	0.33	2.1	3.1	2	23.9
71450D/71750	114.3	190.5	101.6	98.425	1	125	171	1.6	3.2	0.42	1.6	2.4	1.6	11
HH224346D/HH224310	114.3	212.725	152.4	142.885	1	127	191	3.2	3.2	0.33	2.1	3.1	2	21.9
95474D/95925	120.65	234.95	152.4	139.7	1	146	212	6.4	3.2	0.37	1.8	2.7	1.8	28.1
48290D/48220	127	182.562	76.2	76.2	1	136	167	3.2	1.6	0.31	2.2	3.3	2.2	6.7
48290TD/48220	127	182.562	76.2	76.2	2	136	167	1.6	1.6	0.31	2.2	3.3	2.2	6.7
67388D/67322	127	196.85	92.075	92.075	1	145.8	180.1	3.2	1.6	0.34	1.96	2.92	1.92	10.4
67388D/67320	127	203.2	92.075	92.075	1	145.8	180.1	3.2	1.6	0.34	1.96	2.92	1.92	11.8
95499D/95925	127	234.95	152.4	139.7	1	147	212	5	3.3	0.37	1.8	2.7	1.8	26.7
EE153053D/153097	127	247	171.45	161.925	1	153.2	217.4	3.2	3.2	0.32	2.1	3.13	2.05	35.9
95499D/95975	127	247.65	152.4	139.7	1	150.6	204.3	3.2	5.2	0.37	1.83	2.72	1.79	32.4
EE153053D/153100	127	254	171.45	161.925	1	146	223	3.2	6.4	0.32	2.1	3.1	2.1	36.5
EE153053D/153101	127	258.763	171.45	161.925	1	153.2	217.4	6.4	3.2	0.32	2.1	3.13	2.05	41.6
EE153053D/153102	127	260.35	171.45	161.925	1	153.2	217.4	6.4	3.2	0.32	2.1	3.13	2.05	42.5
HH231637D/HH231610	127	288.925	158.75	149.225	1	172.1	252.1	6.4	13.2	0.32	2.12	3.15	2.07	50.9
HH231637D/HH231615	127	295.275	158.75	149.225	1	172.1	252.1	6.4	13.2	0.32	2.12	3.15	2.07	54.3
74510D/74850	130.005	215.9	123.825	123.825	1	145	195	3.2	1.6	0.49	1.4	2.1	1.4	17.2
74510D/74856	130.005	217.488	123.825	123.825	1	153.1	193.4	3.2	1.6	0.49	1.38	2.06	1.35	17.8
74512D/74850	130.175	215.9	101.6	101.6	1	145	195	1.6	3.2	0.49	1.4	2.1	1.4	14.7
74512D/74856	130.175	217.488	101.6	101.6	1	153.1	193.4	3.2	1.6	0.49	1.38	2.06	1.35	15
73512D/73875	130.175	222.25	53.975	60.579	1	160.8	197.9	3.2	3.6	0.44	1.54	2.3	1.51	9.38
67390D/67322	133.35	196.85	92.075	92.075	1	142	180	1.6	3.2	0.34	2	2.9	1.9	9.3
67390TD/67322	133.35	196.85	92.075	92.075	2	145.8	180.1	3.2	1.6	0.34	1.96	2.92	1.92	9.46
67392TD/67322	133.35	196.85	120.65	120.65	2	145.8	180.1	3.2	1.6	0.34	1.96	2.92	1.92	11.6
67390D/67320	133.35	203.2	92.075	92.075	1	145.8	180.1	3.2	1.6	0.34	1.96	2.92	1.92	10.9
67390TD/67320	133.35	203.2	92.075	92.075	2	145.8	180.1	3.2	1.6	0.34	1.96	2.92	1.92	10.9
67392TD/67320	133.35	203.2	120.65	120.65	2	145.8	180.1	3.2	1.6	0.34	1.96	2.92	1.92	13.5